

SW-225 Training Wheel


- Material: Steel Stay / Rubber Tire
- Fit 12" ~ 20" bikes.



SW-225F
with Plastic Rim



SW-225G
with Steel Rim



SW-229 Training Wheel


- Material: Steel Stay / Rubber Tire
- Fit 16"~20" bikes.



SW-229F
with Plastic Rim



SW-229G
with Steel Rim



SW-238 Training Wheel


- Material: Steel Stay / Rubber Tire
- Fit 20" bikes.



SW-238F
with Plastic Rim



SW-238G
with Steel Rim



SW-222 Training Wheel


- Material: Steel Stay / Rubber Tire
- Fit 12"~ 20" / 16"~20" bikes.
- Standard steel stay thickness: 2.8mm.
- TÜV approved steel stay thickness: 3.5mm.
(SW-222FISO / SW222GISO)



SW-222F
with Plastic Rim



SW-222G
with Steel Rim



SW-223 Training Wheel


- Material: Steel Stay / Rubber Tire
- Fit 12"~16" / 12"~20" bikes.



SW-223F
with Plastic Rim



SW-223G
with Steel Rim



SW-224 Training Wheel


- Material: Steel Stay / Rubber Tire
- Fit 12"~20" BMX / 12"~16" MTB.
- Standard steel stay thickness: 2.8mm.
- TÜV approved steel stay thickness: 3.5mm.
(SW-224FISO / SW224GISO)



SW-224F
with Plastic Rim












SW-224G
with Steel Rim






Brackets of Training Wheel

FIT MODEL: SW-222, 223, 228, 230, 231 & 233.

 <p>J1 For attaching on the flange nut of rear hub axle.</p>	 <p>J2 Standard bracket.</p>	 <p>J3 (Standard) For attaching on the thicker hexagonal nut of rear hub axle.</p>
 <p>JS For attaching on the thinner hexagonal nut of rear hub axle.</p>		
 <p>N1 Short cross bracket fixed on the chain stay, for MTB with coaster brake.</p>	 <p>N2 Longer cross bracket fixed on the chain stay, for MTB with hand brake.</p>	 <p>N3 Cross bracket fixed on the chain stay, for MTB bike.</p>
 <p>J5R / J5L For attaching on the dropout of MTB bike. For right & left two sides.</p>		 <p>L For outside attaching on the convex "C" shape stay.</p>

FIT MODEL: SW-303

 <p>A Standard bracket.</p>	 <p>A2 For easy pushing upwards and no conflict with the seat stay.</p>	 <p>D Attaching on the dropout of MTB bike.</p>
---	---	--

WHEEL SIZE & SCREW CAP

				
D 126mm	E 126mm	F 131mm	F3 131mm	G 131mm



FIT MODEL: SW-A011

 <p>A011 Bracket fixed on the chain stay 19mm.</p>	 <p>A011-1 Bracket fixed on the chain stay 26mm.</p>
 <p>A011L Bracket fixed on the chain stay 20mm.</p>	

SW-303D(E) Training Wheel

- Material: Steel Stay / Plastic Rim / PVC Tire
- Fit 12" / 14" / 16" / 18" / 20" bikes.



SW-323D(E) Training Wheel

- Material: Steel Stay / Plastic Rim / PVC Tire
- Fit 12"~14" / 14"~16" / 16"~18" / 18"~20" bikes.



SW-A011 Training Wheel

- Material: Steel Stay / Rubber Tire
- Fit 12"~20" BMX / 12"~16" MTB.
- Standard steel stay thickness: 2.8mm.
- TÜV approved steel stay thickness: 3.5mm. (SW-A011FISO / SWA011GISO)

